


India's No.1 Cables & Wires Company

Dial Polycab for the clearer conversations

State-of-the-Art Telephone Wire Range



Product:	Telephone(Switchboard) Cables
Reference to Standard:	ITD specifications S/WS 113C and Polycab specifications
IS Licence No.:	Not applicable
Copper Type:	Drawn from 8mm Wire Rod-Electrolytic Cathode Grade of 99.97% purity
Reference to IS Standard for Conductors	IS 8130 :1984 with latest amendments
Conductor Construction and type for all sizes:	Single Solid in 0.4mm and 0.5mm Conductor Size
Conductor Construction and type manufactured against Order:	Single Solid in 0.6mm and 0.7mm Conductor Size
Standard Insulation Base:	Special grade High Density Polyethylene
Standard Jacketing Base:	Jacketing of FR (Flame Retardant) PVC Compound made from Virgin Grade PVC resin
Insulation Type for all sizes:	Single coloured pressure extrusion
Jacketing Type for all Pairs:	Generally Tubular Extrusion
Rip Cord:	Nylon

TELEPHONE (SWITCH BORD) CABLE

SR.NO	SIZE	OVER ALL OD MM $\pm$ 0.5 MM	Coils /Master cartoon (Std Packing)	100 METER COILS WEIGHT KG	Available Max. Gross wts on Master Cartoon	RESISTANCE OHM/KM
1	1 PAIR X 0.4 MM	2.30	20	0.70	18.0	143
2	2 PAIR X 0.4 MM	2.90	20	1.1	26.0	143
3	3 PAIR X 0.4 MM	3.40	16	1.5	24.0	143
4	4 PAIR X 0.4 MM	3.80	12	1.8	21.6	143
5	5 PAIR X 0.4 MM	4.20	8	2.2	17.6	143
6	1 PAIR X 0.5 MM	2.60	20	1.1	22.0	92.2
7	2 PAIR X 0.5 MM	3.30	20	1.6	36.0	92.2
8	3 PAIR X 0.5 MM	3.80	16	2.1	33.6	92.2
9	4 PAIR X 0.5 MM	4.50	12	2.4	28.8	92.2
10	5 PAIR X 0.5 MM	4.90	8	3.0	24.0	92.2

Note : Now all 100mtrs coils are packing in HM Bags

Standard Printing on cables:	POLYCAB-TEL NO. OF PAIR X DIAMETER Of CONDUCTOR IN MM - POLYCAB DAMAN
Standard Colours of sheathing available in each size:	Grey
Non-Standard Colours made against bulk orders:	As required
Process Highlights:	On-line Wire Drawing and annealing
Salient Features:	Low Attenuation, Low Cross Talk and Fire Retardent Jacket
Packaging Details:	
a) Mono-Carton for 100mtrs coil	Individual coils of 100 metres packed in 4-colour printed 3-ply corrugated Mono-Carton
b) Master Carton for Standard Pack of 100mtrs coils	Master pack of coils of 100mtrs packed in 2-colour printed 5-ply corrugated Master-Carton

*Note : The conductor construction given above is indicative only and will be such that all requirements of strands, diameter and resistance of conductor as per Referred Standards are met.

Disclaimer: The above data is indicative only and is subject to revision without prior notice. POLYCAB will not be liable for any damages arising out of incorrect application of its products



India's No.1 Cables & Wires Company



POLYCAB WIRES PVT. LTD. Polycab House, 771, Mogul Lane, Mahim (W), Mumbai 400 016.
Tel. : 91-22-2432 7070 - 4, 6735 1400 • Fax : 91-22-2432 7075
• Website: www.polycab.com • E-mail: info@polycab.com